



POSITION/EVENT REPORTING

ACCURATE, SECURE AND RELIABLE

- Secure position reporting
 - Time, location, SOG, COG
 - Variable reporting interval based on
 - In/out of a geo-zone
 - Vessel at rest/in motion
- Secure event reporting
 - Power on/off
 - Signal loss
 - Vessel in/out of a geo-zone
 - Vessel at rest/in motion
- Reports are secure from
 - Tampering
 - Interception
 - Spoofing
- Map based fleet tracking available



CATCH REPORTING

SEND/RECEIVE REPORTS ANYTIME

- Transmit forms to shore
- Increase the efficiency of billing and information flow



EMAIL/SMS

STAY CONNECTED

- Send and receive emails/SMS from any location
- Small attachments available



WEATHER ON DEMAND

UP-TO-DATE WEATHER FORECASTS

- Request weather forecasts on demand
- View wave height, wind speed and direction, barometric pressure, temperature, for any location



SOS

GLOBAL SEARCH AND RESCUE

- 2-way communication with global SAR
- Automatic position updates to SAR



REMOTE MONITORING

PEACE OF MIND

- Monitor up to 16 sensors
- Emergency notifications
- Easy to setup customizable rules



LOW MONTHLY COST

FLEXIBLE AND AFFORDABLE

- SkyMate gives more for less!



USER FRIENDLY

EASY TO INSTALL AND OPERATE

- Available with dedicated display, stand alone system, or open to any device with a browser
- DIY install and quick setup
- Plug-and-play right out of the box

Communications Hub



Smart Antenna



Keypad

- Message Waiting Indicator
- Sentry Monitoring Switch
- Emergency Notification



Accessories/Options

- Sentry remote monitoring
- 10m antenna extension cable
- 10m keypad extension cable
- 2m NMEA 2000 cable



ENVIRONMENTALS

- Operating: -25°C to 55°C
- Non-Operating: -35°C to 60°C
- IEC 60945, EN 60529, IP67

POWERMANAGEMENT

- For operation in both nominal 12V and 24VDC battery systems
- Less than 5W power required (fully configured)
- Reverse wiring polarity protection
- Continuous over-voltage protection

CONFIGURATIONMANAGEMENT

- Firmware updates over satellite and via terminal

SYSTEM FEATURES

- Integrated audio notifications (buzzer)
- Customizable Geo-fencing
- Global Search and Rescue
- NMEA 2000, USB, Wi-Fi, BLE communications capability



COMMUNICATIONS HUB

- 57mm(H) x 133mm(W) x 133mm(L)
- Weight 0.50kg
- Vertical or horizontal mounting bracket provided
- 2m power cable with USB
- Wi-Fi access point
- LED status indicators
- Internal battery for monitoring and emergency operation

SMART ANTENNA

- 94mm(H) x 127mm(W) x 54mm(L)
- Weight 0.72kg
- Surface or pole mounting options
- 10m CAT5 cable (can be extended up to 30m)
- Dual Iridium/GPS antenna

KEYPAD

- 13mm(H) x 102mm(W) x 102mm(L)
- Weight 0.20kg
- Adhesive or bolt mounting options
- 2m cable (can be extended up to 12m)



SkyMate 11890 Sunrise Valley Dr., Suite 100, Reston, VA 2019
 PH: 703-961-5800 | PH: 866-SkyMate | sales@SkyMate.com

www.SkyMate.com